

Specifications

Processing	
CPU	14K DMIPS, quad-core ARM-v8 CPU
DRAM	1GB or 2GB RAM
Flash	8GB iNAND
Software	
Operating System	Linux
Audio / Video Interfaces	
Digital Video	HDMI 2.0
Analog Video	CVBS + L/R Audio
Video Formats	
Video Resolutions	480i, 480p, 576i, 576p, 720p, 1080i, 1080p60, 2160p60 10-bit
Audio Codecs	Dolby Digital, Dolby Digital Plus, MPEG I Layer 1 and 2, LC-ACC & HE-AAC
Video Codecs	AVC/H.264 High Profile @ Level 4.2, HEVC/H.265, MPEG-1/H.261/H.263, MPEG-2 Main Profile @ High Level, VP9
Other codecs on request	

Other Interfaces	
Ethernet	10/100/1000 Base-T Ethernet
Wi-Fi	4x4 802.11ac/n 5GHz
USB	1 x 3.0
Status LED	Standby button with status LED
Remote Control Support	IR 36KHz / BLE
Regulatory Compliance	
Environment and Safety	FCC Certified, CB Certified, CE Certified, RoHS Compliant
Power	
Power Supply	External, 12V / 2A
Power Consumption	7W maximum, fully equipped
Operating Environment	
Temperature	5-40°C (40-104°F) operating temperature
Humidity	30-95% relative humidity
Physical Properties	
Size (L*W*H)	170 mm x 117 mm x 36 mm
Weight	270g



Kamai 7B

Powerful 4K UHD client Device with Advanced WiFi Options

